

→ Impianto iperfiltrazione inversa a flusso diretto

HYDRO LIFE 600 GPD

CARATTERISTICHE

PRODUZIONE NOMINALE	100 L/H (+/- 10%)
SALINITÀ RIGETTATA	9.5 / 98% (+/- 10%)
FILTRO	Combi (PP / BLOCK)
MEMBRANA	Iperfiltrazione 600 GPD
POSTFILTRO	Combi (PP / BLOCK)
MOTORE	Pompa Booster 24 VDC
ALIMENTATORE	230 Vac 50 / 60 Hz: 24 Vdc
CENTRALINA	Controllo funzioni
AUTOFLUSHING	Multiplici membrane iperfiltrazione
LED DI SEGNALEZIONE	Esaurimento filtri, membrana iperfiltrazione e avarie
DIMENSIONI	138 x 375 x 435 mm
PESO	12 kg

COMPONENTI IN DOTAZIONE

Rubinetto 1 via Led
Componenti per installazione
Frontalino incluso da settembre 2022



**FILTER
CONTROL**



**QUALITY
CONTROL**



**SOUND
WARNINGS**



**SMART
FAUCET**



**LED
STATUS**



**HIGH PERFORMANCE
MOTOR**




**HIGH
EFFICIENCY**



138mm

435mm

375mm



WLG (B-60326279), is member of the Water Quality Association.



ACREDITED BY ENAC
Certif. nº 34/5200/14/0712

The trading of water treatment and household appliances as well as designing and teaching of non-official training courses related with its technology are certified and comply with the UNE-ISO-9001 for WLG (B-60326279).



WLG (B-60326279) is an Aqua España member, who belongs Aqua Europa (Federation of European nation associations).



WLG (B-60326279), has the rights granted for Authorized Economic Operator with number ESAEOF18000008U6 and 13/02/2018 as a date of entry of the authorization.